

Customer display **WD-202**

Blue-green vacuum fluorescent display features:

- ⊙ Data can be display on 20 columns X 2 lines.
- ⊙ Display panel is adjustable to provide the best view angle.
- ⊙ Provide 2 pole for best position installation.
- ⊙ Esc/pos command compatible.
- ⊙ International character set is selectable.
- ⊙ User-defined characters can be downloaded.
- ⊙ User-defined message can be download.
- ⊙ Green power function.
- ⊙ Provides interface on RS-232C , USB for option.
- ⊙ Built-in pass through function.



General Specifications:

Power supply	DC 9 ~ 35 V	Power consumption	3 ~ 6 W	
Character	20 columns X 2 lines	MTBF (power on time)	25000 hours	
Display color	Blue green	Viewing angle	0 ~ 45 degrees	
Brightness	700 cd/m ²	Rotation angle	Maximum 270 degrees	
Character font	5 X 7 dot matrix	Weight	0.90 Kg	
Character size	9.0mm X 5.25mm	Environmental condition:		
Character type :	96 alphanumeric		Temperature	Humidity
	13 kinds of international character set	Operating	5 ~ 45 °C	30% ~ 85%
	1 kind of user define character	Storage	-10 ~ 55 °C	30% ~ 85%

Overall Dimensions:

