

Thermal Printer

# LK-T21

## High quality thermal receipt printer

Ideal for POS system & Lottery system

Easy drop-in paper loading

Adjustable paper width (50mm ~ 82.5mm)

High speed performance (200mm per second)

### Easy Load, Drop-In & Print



### Interface



### Wall mount available



## LKT SERIES SPECIFICATION



<b>MODEL</b>		LK-T21
<b>PRINT METHOD</b>		Direct Thermal
<b>PRINTING SPEED</b>		200mm/sec
<b>DOT DENSITY</b>		180 DPI x 180 DPI
<b>DOT PITCH</b>		0.141mm x 0.141mm
<b>EFFECTIVE PRINTING WIDTH</b>		72mm, 512 Dots/Line
<b>PRINTING DIRECTION</b>		Unidirectional with friction feed
<b>CHARACTER PER LINE</b>		Font A(12 x 24) 42 columns / Font B(9 x 17) 56 columns
<b>PAPER</b>	<b>TYPE</b>	Thermal paper
	<b>WIDTH</b>	50mm ~ 82.5mm
	<b>THICKNESS</b>	0.06 ~ 0.09mm
	<b>ROLL DIAMETER</b>	Max. Ø83.0mm
	<b>ROLL CORE INNER DIAMETER</b>	12.5mm ± 0.5mm
<b>RELIABILITY</b>	<b>TPH LIFE</b>	100 km
	<b>MCBF</b>	60,000,000 Lines
<b>CHARACTER SET</b>	<b>ALPHA NUMERIC CHARACTER</b>	95
	<b>EXTENDED GRAPHIC</b>	128 x 18 page(1 space page)
	<b>INTERNATIONAL CHARACTER</b>	14
<b>BARCODE</b>		EAN-8, EAN-13, CODE39, ITF, UPC-A, CODABAR, CODE93, CODE128, PDF417(2D)
<b>EMULATION</b>		ESC/POS COMMAND COMPATIBLE
<b>DRIVER</b>		Windows Printer Driver(XP, 2000, 2003, WEPOS) OPOS, Linux
<b>SENSOR</b>		Paper end sensor, Cover open sensor Black mark sensor, Paper low sensor
<b>CASH DRAWER DRIVER</b>		2 circuits(24V, 1A max)
<b>INTERFACE</b>		Serial(RS-232C), Parallel(IEEE-1284), USB, Ethernet, WiFi, USB Combo
<b>POWER</b>	<b>TYPE</b>	External SMPS
	<b>AC</b>	100 ~ 240Vac 50/60 Hz
	<b>DC</b>	24Vdc / 2.5A
<b>DIMENSION</b>	<b>Wmm x Dmm x Hmm</b>	152 x 204 x 150
	<b>W" x D" x H"</b>	5.98 x 8.03 x 5.9
<b>AUTO CUTTER</b>	<b>TYPE</b>	Guillotine
	<b>LIFE</b>	1,000,000 cuts
	<b>PAPER THICKNESS</b>	0.06 ~ 0.09mm
	<b>CUTTING METHOD</b>	Full/Partial Cut
<b>WEIGHT</b>	<b>INCLUDE AUTO CUTTER</b>	1.7 kg
<b>TEMPERATURE</b>	<b>OPERATING TEMPERATURE</b>	5 ~ 40°C
	<b>STORAGE TEMPERATURE</b>	-20 ~ 60°C
<b>HUMIDITY</b>	<b>OPERATING HUMIDITY</b>	35 ~ 80%
	<b>STORAGE HUMIDITY</b>	10 ~ 90%

Specifications are subject to change without notice.

January 2007



SEWOO TECH Co., Ltd.

Doosung Bd, 689-20, Kumjung-dong,  
Kunpo-si, Kyunggi-do, Korea